



HOUSING  
 Part No:KJ-2541H  
 Material:Nylon66 UL94-V2,Beige  
 Circuits:2-20  
 Insulation Resistance:1000MΩ min  
 Withstand Voltage:1000V AC/minute  
 Current Rating:4A AC,DC  
 Voltage Rating:250V AC,DC  
 Temperature Range:-25°C ~+85°C

RoHS

Dimensions

circuits	A	B	circuits	A	B
2	2.54	5.68	12	27.94	31.08
3	5.08	8.22	13	30.48	33.62
4	7.62	10.76	14	33.02	36.16
5	10.16	13.30	15	35.56	38.70
6	12.70	15.84	16	38.10	41.24
7	15.24	18.38	17	40.64	43.78
8	17.78	20.92	18	43.18	46.32
9	20.32	23.46	19	45.72	48.86
10	22.86	26.00	20	48.28	51.40
11	25.40	28.54			

東莞嘉英電子廠 JIA YING ELECTRONICS		UNIT:MM		繪圖 DRAWING:	黃玲麗	比例 (SCALE):	7:1
		ANGLE ±2°	DIM: .X±0.50 .XX±0.25 .XXX±0.10	審核 CHECKED BY	凌輝	名稱 (TITLE):	MX2.54 HSG
DESCRIPTION:	MX2.54 HSG	REV:A2		核准 APPROVAL BY	苗德蕙	存檔名稱 (FILE):	KJ-2541H
PART NO:	KJ-2541H			日期 (DATE):	2010/02/02	PROJECTION:	